



Isolatoren 6 hoek

TYPE ISO-TP 6 hoek



code Nr.	artikel		B	L(mm)	sw	prijs p/st
548400	ISO TP 15	M4	12	15	16	2,00
548410	ISO TP 20	M4	15	20	20	2,14
548420	ISO TP 20	M6	15	20	20	2,14
548700	ISO TP 25	M5	18	25	20	2,61
548430	ISO TP 25	M6	18	25	20	3,98
548440	ISO TP 30	M6	26	30	34	3,98
548450	ISO TP 30	M8	26	30	34	3,98
548470	ISO TP 35	M6L	34	35	46	4,43
548480	ISO TP 35	M8	34	35	46	5,20
548490	ISO TP 35	M10	34	35	46	5,20
548500	ISO TP 40	M6	40	40	53	5,96
548510	ISO TP 40	M8	40	40	53	6,26
548520	ISO TP 40	M10	40	40	53	6,26
548511	ISO TP 40	M12	40	40	53	6,26
548530	ISO TP 45	M6	34	45	47	6,26
548540	ISO TP 45	M8	34	45	47	6,26
548550	ISO TP 45	M8L	41	45	57	7,17
548560	ISO TP 45	M10	41	45	57	7,47
548570	ISO TP 50	M6	41	50	57	8,08
548580	ISO TP 50	M8	41	50	57	8,90
548590	ISO TP 50	M10	41	50	57	8,59
548581	ISO TP 50	M12	41	50	57	8,40
548600	ISO TP 60	M8	44	60	57	8,93
548610	ISO TP 60	M10	44	60	57	9,97
548601	ISO TP 60	M12	44	60	57	13,75
548602	ISO TP 60	M16	44	60	63	16,62
548609	ISO TP 70	M10	52	70	63	9,93
548620	ISO TP 70	M12	52	70	63	16,62
548630	ISO TP 70	M16	52	70	63	16,77
548629	ISO TP 75	M10	51	75	75	16,77
548640	ISO TP 75	M12	51	75	75	16,77
548650	ISO TP 75	M16	51	75	75	18,28
548660	ISO TP 80	M12	52	80	75	23,96
548670	ISO TP 80	M16	52	80	75	24,54
548680	ISO TP 100	M12	46	100	75	26,22
548690	ISO TP 100	M16	46	100	75	27,46

Materiaal:

PA glasvezel versterkt
 Treksterkte van 150-3000 daN
 Buigsterkte van 100- 1500 daN
 Wisselspanning van 500/1000 V
 Gelijkspanning van 500/1500 V
 CE conform, RoHS 2002/95/EC, IEC 60 439.1,
 UL geaccepteerd E 125470
 Zelfdovend volgens UL 94 VO